

Please type a plus sign (+) inside this box → ☐

Approved for use through 09/30/00. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. **044463.0014**
First Named Inventor or Application Identifier **Crescenti, et al.**
Title **Hierarchical Backup and Retrieval System**
Express Mail Label No. **EJ199973991US**

APPLICATION ELEMENTS
See MPEP Chapter 600 concerning utility patent application contents

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original, and a duplicate for fee processing)

6. ☐ Microfiche Computer Program (Appendix)

2. ☒ Specification [Total Pages **29**]
(preferred arrangement set forth below)

7. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)

- Descriptive title of the Invention
- Cross References to Related Applications
- Statement Regarding Fed sponsored R&D
- Reference to Microfiche Appendix
- Background of the Invention
- Brief Summary of the Invention
- Brief Description of the Drawings (if filed)
- Detailed Description
- Claim(s)
- Abstract of the Disclosure

a. ☐ Computer Readable Copy

b. ☐ Paper Copy (identical to computer copy)

c. ☐ Statement verifying identical of above copies

3. ☒ Drawing(s) (35 USC d113) [Total Sheets **5**]

4. Oath or Declaration (including Supplemental Declaration) [Total Pages **3**]

a. ☐ Unexecuted

b. ☐ Copy from a prior application (37 CFR §1.63(d))
(for continuation/divisional with Box 17 completed)

[Note Box 5 below]

i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s)
named in the prior application,
see 37 CFR §1.63(d)(2) and 1.33(b).

5. ☐ Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of
the oath or declaration is supplied under Box 4b, is considered as
being part of the disclosure of the accompanying application and is
hereby incorporated by reference therein

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & Documents(s))

9. ☐ 37 CFR §3.73(b) Statement (when there is an assignee) ☒ Power of Attorney

10. ☐ English Translation Document (if applicable)

11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations

12. ☐ Preliminary Amendment

13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)

14. ☐ Small Entity Statement(s) ☐ Statement filed in prior application
(PTO/SB/09-12) Status still proper and desired

15. ☐ Certified Copy of Priority Document(s)
if foreign priority is claimed

16. ☐ Other:

*A new statement is required to be entitled to pay small entity fees, except where one has been filed in a prior application and is being relied upon.

17. If a **CONTINUING APPLICATION**, check appropriate box and supply the requisite information below and in a preliminary amendment:


☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP)

Prior application information: Examiner _____ Group / Art Unit: _____

18. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label (Insert Customer No. or Attach bar code label here) or ☒ Correspondence address below

NAME	James D. Bennett		
	Akin, Gump, Strauss, Hauer & Feld, L.L.P.		
ADDRESS	816 Congress Avenue, Suite 1900		
CITY	Austin	STATE	Texas
COUNTRY	U.S.A.	TELEPHONE	(512) 499-6200
		ZIP CODE	78701
		FAX	(512) 499-6290

Name (Print/Type)	J. Davis Gilmer	Registration No. (Attorney/Agent)	P-44,711
Signature		Date	7/15/99

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

044463.0014 AUSTIN 129615 v1



PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

(Attorney Docket No. 044463.0014)

TITLE

HIERARCHICAL BACKUP AND RETRIEVAL SYSTEM

INVENTORS

John Crescenti

1 Ivy Road
Freehold, NJ 07728

Srinivas Kavuri

40 Maple Court
Highland Park, NJ 08904

David Alan Oshinsky

22 Francis Road
East Brunswick, NJ 08816

Anand Prahlad

3 Bucknell Drive
East Brunswick, NJ 08816

ASSIGNEE

CommVault Systems, Inc.

2 Crescent Place
Oceanport, N.J. 07757-0090

CERTIFICATE OF EXPRESS MAILING

I hereby certify that this correspondence, which includes 29 pages of Specification and 5 pages of Drawings, is being deposited with the United States Postal Service "Express Mail Post Office to addressee" Service under 37 C.F.R. Sec. 1.10 addressed to: Box Patent Application, Assistant Commissioner for Patents, Washington, D.C. 20231, on July 15, 1999.

Express Mailing Label No.: EJ199973991US


Teresa A. Newby

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
(Attorney Docket No. 044463.0014)

TITLE: HIERARCHICAL BACKUP AND RETRIEVAL SYSTEM

CROSS REFERENCE TO RELATED APPLICATIONS

This application is related to another application entitled "MODULAR BACKUP AND RETRIEVAL SYSTEM", filed July 15, 1999, U.S. serial number -----, in the names of Crescenti, Oshinsky, Kavuri, and Prahlad, and assigned to the assignee of this invention. This related application entitled "MODULAR BACKUP AND RETRIEVAL SYSTEM" is incorporated hereby by reference .

BACKGROUND OF THE INVENTION

1. Technical Field

The present invention is directed to storage and retrieval systems. In particular, the invention is directed towards a hierarchical storage and retrieval system for a computer or a series of interconnected computers.

2. Related Art

Conventional backup devices usually employ a monolithic backup and retrieval system servicing a single server with attached storage devices. These systems usually control all aspects of a data backup or retrieval, including timing the backup, directing the files to be backed up, directing the mode of the archival request, and directing the storage

are not scalable and often direct only one type of backup and retrieval system, whether it is a network backup or a single machine backup.

If a backup software program failed for a particular computing device, a chance exists that the information for the backup suite would also be lost. Information about the activities of the backup program may be corrupted or lost. Additionally, without reinstallation, the backup program could not direct the backup of the particular computing device, and important information may not be backed up until the re-establishment of the backup program on the computing device.

Further, with distributed computing devices, it is necessary to micromanage each backup program on each computing device to maintain consistency in the backup activities of all backup programs. No external control can be asserted over multiple backup programs from a centralized location. Many other problems and disadvantages of the prior art will become apparent to one skilled in the art after comparing such prior art with the present invention as described herein.

SUMMARY OF THE INVENTION

Various aspects of the present invention may be found in a backup system for a network computing system. The network computer system has a first network device and a second network device. The backup system has a first software agent operating on a first network device on the network computing system. The first software agent is communicatively coupled to at least one backup device. The first software agent maintains operational parameters for the backup regime for the network computer system. The first software agent makes archival requests directed to the backup device or devices to initiate archival requests, including backups and restores.

A second software agent, operating on the second network device, supervises the operation of the first software agent. The second software agent is able to initiate archival function requests to the backup device or devices independent from the first software agent. Additionally, the second software agent may make an archival request directly to the first software agent, which then initiates the actual request directed to the backup device. The backup system of claim 1 wherein the first software agent is responsive to archival function requests from the second software agent. Or, the second software agent may change the operational parameters of the first software agent, thus allowing the second software agent to set administrative control of the backup of the network computing devices.

The first software agent communicates information on the status of the backup device or devices that it is responsible for to the second software agent. The first software agent may also communicate the status of the network computing devices that it is responsible for the backup of to the second software agent. This allows the second

software agent to stand in for the first software agent when the first software agent is unable to perform at its full functionality. The second software agent is able to manage the backup of the network computing devices that the first software agent is responsible for when the first software agent is unable to do so.

In an exemplary embodiment, the network computer system has a first group of network computing devices. A manager software component runs on a network device and is responsible for managing parameters describing the archival characteristics of the first group of network devices, as well as able to initiate archival requests for those network computing devices.

The manager software component is communicatively coupled to at least one, possibly more, backup devices that physically perform the archival requests at the behest of instructions from the manager software component. A second software component supervises the manager software component, and is able to initiate a change in the operational parameters as described by the manager software component. Thus, the second software component may administer the characteristics of the backup policy of the manager software component.

In one embodiment, the second software component executes on a second network device, or it may also execute on the network device on which the manager component is executing. In an embodiment, the second software component is itself a manager software component responsible for the backup policies of a second group of network devices.

Or, the manager software component can operate the backup activities of a backup cell. Additionally, the second software component can operate the backup activities of a

second backup cell, as well as manage or supervise the manager software component operating the first cell. Thus, a hierarchical structure in a backup system can be defined.

In another embodiment, the network computer system has a first group of network devices. The backup system has defined domains.

The first domain has a first manager software agent executing on a first network computing device. The first manager software agent is responsible for managing backup activities for the first group of network devices. The backup activities are coordinated with a backup device or devices that is in communication with the first manager software agent. These backup devices respond to the archival requests of the first manager software agent to carry out a backup policy for the first group of network devices.

A second domain has a second software agent, which administers the activities of the first manager software agent. The second software agent receives information on the first domain, and as such, the second software agent may operate the backup activities of the first domain.

The second software agent can manage a second group of network devices in the second domain in a similar manner to the first manager software agent operating and managing the first domain. As such, many other domains can be defined, and may be placed in communication with other domains. The manager software agent of each domain may be responsible for administratively managing other domains, and may in turn be managed by manager software agents in other domains. Many different control structures can be built with this interconnectivity of domains.

The information on a domain may be passed to another manager software agent responsible for another domain. The parent manager software agent may be able to pass

instructions to the child domain and its manager software agent. As such, the parent manager software agent can operate the domain, or may be able to administer the child manager software agent's management of the domain.

Further, the second manager software agent may execute on the same network device as the first manager software agent. Alternatively, the second manager software agent may execute on a different network device as the first manager software agent.

Other aspects of the present invention will become apparent with further reference to the drawings and specification that follow.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram of a hierarchical network backup system according to the invention.

Fig. 2 is functional block diagram of an embodiment of the hierarchical backup system of Fig. 1 embodying data transfer between the components comprising the individual backup cell and the transfer of data outside of the backup cell.

Fig. 3 is a block diagram detailing the use of the manager component of Fig. 1 as a virtual manager component for a plurality of virtual backup cells.

Fig. 4 is a logical block diagram of the resulting backup cells of the network system depicted in Fig. 3.

Fig. 5 is a block diagram of an exemplary hierarchical backup network according to the invention.

DETAILED DESCRIPTION OF THE INVENTION

Fig. 1 is a block diagram of a hierarchical network backup system according to the invention. A backup cell 100 comprises a plurality of network devices 110, 120, and 130 that are to be backed up. The backups of the network devices are made to the attached backup devices 112, 122, and 132.

The network device 110 contains a manager component 114. The manager component 114 is a software agent responsible for the maintaining backup parameters of the backups in the backup cell 100, and initiating a backup policy for the attached network computing devices according to those parameters. The parameters can include schedules of backups, aging policies, pruning policies, and backup media usage policies. Thus, through the operation of the manager component 114, an administrator can define the characteristics of the backup actions for the network computing devices associated with the backup cell 100.

Connected to and in communication with the backup cell 100 is a backup cell 150, comprising a plurality of network devices 160, 170, and 180. These network devices are also subject to backing up to the backup devices 162, 172, and 182.

The network device 160 contains a manager component 164 that is responsible for the backup parameters of the backups in the backup cell 150. The manager component 164 is similar in operation and in functionality to the manager component 114 in the backup cell 100. Thus, through the operation of the manager component 164, an administrator can define the characteristics of the backup actions for the backup cell 160.

In the case where the network 140 connecting the network devices 110, 120, and 130 is not suitable based on speed and/or reliability, the size and scope of the backup cell

100 may be limited. Or, the site at which the backup cell 100 is physically located may not have an administrator present with the background, ability, or authority to modify the backup parameters of the backup cell 100. Or, having a single point of failure, namely the network device 110 or the manager component 114 may not be an acceptable alternative to the user of the backup cell 100.

As such, the manager component 164 of the backup cell 150 is placed in communication with the backup cell 100. The manager component 164 running on the network device 160 is given the authority, power, and ability to maintain and control the backup parameters and actions on the backup cell 100. Further, information on the status of the network devices, the backup devices, and on the manager component 114 is made known to the manager component 164. Thus, the backup of the network devices 110, 120, and 130 may be maintained and controlled from another software agent at another location, such as the manager component 164. As such, alternative administration may be exercised on the backup characteristics and actions of the backup cell 100 from another backup cell.

Routine activities within the backup cell 100 can take place with little or no interaction with the remote manager component 164. These routine activities include backups of and restorations to the network devices 110, 120, and 130, and administration and/or configuration of the parameters of the archival functionality of the backup cell 100.

Or, interaction with the remote manager component 164 could take place when an administrator who is logged into the network device 160 would like to administer activity that takes place in the backup cell 100. Or, splitting of administrative functionality

between the manger components 114 and 164 could take place, thus centralizing some or all of the definition of the functionality of the backup schemes to a common set of parameters across associated backup cells. Or, the administrative authority of the manager components may be highly decentralized, and the alternative control of another backup cell may be used only when the manager component of another backup has failed for some reason.

Information on the individual components making up the backup cell 100 can be communicated to the manager component 164. Thus, the manager component 164 could, to varying degrees as defined by operational needs, operate or initiate operation of the various components of the backup cell 100.

The manager component 164 could also be configured to change the operational parameters of the manager component 150. Thus, a system wide change to backup cell parameters can be initiated through a single manager component and propogated to other backup cells. Or, the manager component 164 could fill in for the manager component 114 should it fail. Additionally, the interaction between the backup cells and other manager components allows for the appearance of a “seamless” network of backup cells to administrators sitting in remote locations.

Additional supervisory levels, controls, or permissions could be added to the manager component 164 to allow the supervisory control of additional backup cells for which the manager component 114 is supervising. As such, a hierarchy of backup control can be realized through the interaction of levels or connections of manager components.

Additionally, the manager components 114 and 164 can be configured such that critical events are propagated to another manager component having supervisory control

or permission for it. Thus, an administrator logged into a managerial component sitting in the path of propagation can see critical events happening in the backup cells in the path of supervision. This criticality threshold for an event to be propagated to another management component of another backup cell may be configurable. Thus, an individual manager component can track the universe of backup cells that it is communicatively coupled to.

It should be noted that while only one backup cell is pictured in communication with the manger component 164, that any number of backup cells may be envisioned. It should also be noted that the hierarchy of backup cells may be configured in many manners. Thus, a single manager component may associate itself with several other backup cells, in a “shallow” configuration. Or, each succeeding manager component may be associated with one or more other backup cells, providing a tree-like structure to the supervisory capacities of the manager components. Or, a ring-like structure may be envisioned, where each manager component is associated with another backup cell, and the last manager component is associated with the first backup cell.

Further details on structures of a backup cell may also be envisioned by reference to U.S. Patent Application -----, “MODULAR BACKUP AND RETRIEVAL SYSTEM”, filed July 15, 1999. This application is incorporated hereby by reference for all purposes. The details of the backup cell as recited in the reference are substantially similar to that outlined above, but are not detailed in this application.

Fig. 2 is functional block diagram of an embodiment of the hierarchical backup system of Fig. 1 embodying data transfer between the components comprising the individual backup cell and the transfer of data outside of the backup cell. The backup cell

200 comprises the network computing devices 210, 220, and 230. The network computing device 210 runs a manager component 212, responsible for the backup parameters of the backup cell 200, as described before.

The network computing devices 210 and 230 are communicatively coupled to backup devices 218 and 238, respectively. The backup devices 218 and 238 store the data and or files directed to them in a backup, where the data and/or files can be retrieved at a later time.

The backup devices 218 and 238 are operated by media components 216 and 236, respectively. The media component 216 is a software agent responsible for the physical operation of the backup device 218 during a backup or restore. During a backup, the media component 216 maintains an index of the data units and/or files backed up and where they are physically located on the physical backup device 218. The backup device 238 and the media component 236 operate in a similar manner. It should be noted that the backup devices may be many types of devices, including such storage devices as tape drives, cartridge drives, magneto-optical drives, or any combination thereof.

The network computing devices 210, 220, and 230 also contain client components 214, 224, and 234, respectively. The client components 214, 224, and 234 are software agents tasked with maintaining the operational parameters and controlling a backup or restore of an individual network computing device. Thus, the types of files and/or data backed up, the priority of the files and/or data to be backed up, and other operational parameters of a backup for a particular network computing device are controlled by a particular client component.

In a backup, the manager component 212 would indicate to the appropriate client component to initiate a backup, and that the backup should be directed to a particular backup media. For example, assume that the manager component 212 determines that a backup of the network device 220 is warranted. The manager component 212 also determines that the backup should be directed to the backup device 238. The manager component 212 would contact the client component 224 with the request for a backup of the network device 220, and that the data and/or files should be stored through the media component 236 on the backup device 238.

The client component 224 undertakes the backup of the network computing device 220 in an appropriate manner. The backup may be a full backup, an incremental backup, or a differential backup, depending upon the strategy as defined by an administrator for the network computing device 220. The client component 224 would then notify the media component 236 of the data and/or files to be backed up. The media component 236 would cause the data and/or files sent by the client component 224 to be physically backed up on the backup device 238.

The media component 236 makes an index entry for the backed up file and/or data units, thus keeping an easily maintained and coordinated way to manage information on the backup of the file and/or data units, including their whereabouts and other particulars. Portions of the indexed information on the file and/or data units are forwarded to the manager component 212. The manager component may use this information in the managing of the backup devices and the determination of where to send other file and or data units from backups from other network computing devices.

The manager component 212 is able to receive and send this indexed information to the manager component 262 running on the network computing device 260.

Additional indexed information on the backup can exist distributed about the various media components, and the manager components 212 or 262 can access this information by querying the proper media component for it. Thus, the information required to make the proper query can be passed among the manager components as well. The manager component 262 can itself be a manager component for the backup cell where it resides.

While a peer-to-peer relationship can be present among the manager components, the manager components can be configured in a parent-child relationship as well. The manager component 212 can be configured to receive directions from the manager component 262 regarding the operation of the backup cell 200. Additionally, information on the client components 214, 224, and 234 could be provided, as well as information on the media components 216 and 236, and on the backup devices 218 and 238.

Should the manager component 262 running on the network computing device 260 be so configured, this information from the manager component 212 could be propagated to the manager component 262. Thus, complete operational control of the manager component 212 could be asserted from the manager component 262 with the proper authorization.

Further, since the manager component 262 has information about the client components 214, 224, and 234, the information about the media components 216 and 236, as well as information about the media devices 218 and 238, the manager component 262 could operate as a surrogate manager component to the backup cell 200. As such, the

manager component 212 could be bypassed in the event of a failure of the manager component 212.

Additionally, the manager component 262 may be given a supervisory control over the manager component 212. This would enable the manager component 262 to change operational parameters, administration, or configuration of the backup cell 200, or to allow a supervisor sitting at the network device 260 to operate the functionality of the backup cell 200 in the event of an emergency.

Fig. 3 is a block diagram detailing the use of the manager component of Fig. 1 as a virtual manager component for a plurality of virtual backup cells. The backup cells 100 and 150 of Fig. 1 may be “virtual”, as well as physical, backup cells. The virtual manager components can identify administrative domains over which the particular virtual manager component exercises administrative control.

In this case, one physical manager component 310 could be logically divided into several virtual manager components 320, 330, and 340. Each of the virtual manager components 320, 330, and 340 would be responsible for the backup functionality of portions of the physical network devices located in the physical backup cell.

The manager component 310 runs on a network computing device 312. Connected to and in communication with the network computing device 312 are network computing devices 370, 372, 350, 352, 360, and 362.

The network computing devices 370 and 372 are logically grouped together as a unit requiring one particular set of backup guidelines. Similarly, the network computing devices 350 and 352 are logically grouped together as another group of network computing devices requiring another particular set of backup guidelines. Also, the

network computing devices 360 and 362 are logically grouped together as a unit requiring yet another particular set of backup guidelines.

The manager component 310 can be configured to operate three independent backup management policies. The virtual manager component 340 is responsible for the backup management of the group of network devices 370 and 372. The virtual manager component 320 is responsible for the backup management of the group of network devices 350 and 352. The virtual manager component 330 is responsible for the backup management of the group of network devices 360 and 362.

A remote network device 380 operates a manager component 385. The manager component is in communication with the manager component 310. As such, the manager component 310 can be configured to supervise the activities of the manager component 310, and the virtual manager components 320, 330, and 340.

Fig. 4 is a logical block diagram of the resulting backup cells of the network system depicted in Fig. 3. The manager component 340 and the network computing devices 370 and 372 make up a first virtual backup cell 410. Similarly, the manager component 320, along with the network computing devices 350 and 352, make up a second virtual backup cell 420. Also, the manager component 330 and the network computing devices 360 and 362 make up a third virtual backup cell 430.

Each virtual manager component is responsible and maintains the functional parameters associated with the group of network computing devices associated with it. Each virtual manager component within the physical manager component 310 is able to maintain and control the backup and restoration actions and parameters of the network

devices associated with it in a manner independent from the other virtual manager components it is related to.

The virtual manager components may be configured where one of the manager components maintains supervisory control over the others, or any other combination. Or, the remote manager component 385 may maintain supervisory control any of the virtual manager components 320, 330, and 340 and their associated backup cells. Or, as indicated earlier, any or all of the virtual manager components 320, 330, or 340 may be configured to supervise the manager component 385 and its associated backup cell.

As such, the ability to link together similar network devices under different manager components enables a backup system that easily defines domains and sub-domains within an enterprise or organization. Thus, a manager component able to maintain supervisory control over others may be easily maintained and identified in a linked network of virtual and physical backup cells by name.

Fig. 5 is a block diagram of an exemplary hierarchical backup network according to the invention. Each bubble represents a physical backup cell, as described previously. The physical backup cells may contain other virtual backup cells. The backup cells can be configurable by a domain name, which uniquely identifies the location and/or supervisory overview of the backup cell in the hierarchy.

As such, the root backup cell of the network of backup cells can be defined as the domain name "Company", or other identifier indicating the root. In the naming convention, any manager component associated with a particular name would exercise supervisory control over manger components having that name followed by a delimiter, and followed by a sub-domain name. In this case, the manager component within a

backup cell that is the root of a sub-tree of the would be able to exercise supervisory or administrative control over the backup cells further from the root.

Thus, the manager component associated with the “Company” backup cell would exercise supervisory control over the entire tree, including the sub-domains indicated by “Company.hq”, “Company.mktg”, “Company.eng”, and “Company.sales”. Additionally, the manager components under each of the sub-domains would exercise supervisory control over the sub-sub-domains identified with the proper sub-domain prefix.

As such, the domain “Company.hq” may be representative of the an administrative domain located at a company’s headquarters and responsible for backup actions and parameters about the physical headquarters. The managerial component associated with the domain “Company” can exercise supervisory control over the backup cell associated with the domain “Company.hq”.

A backup cell 510 is a backup cell associated with the sales network computing devices. The backup cell 510 contains two different domains, “Company.sales” and “Company.sales.usa” . The domain “Company.sales” is the supervisory domain for the sub-domains existing underneath “Company.sales”. The domain “Company.sales.usa” is associated with a backup cell that manages the backups for network computing devices in the company’s United States sales area. The manager component directing the backup cell “Company.sales.usa” is supervised by the manager component associated with the backup cell “Company.sales”

A backup cell 512 is associated with the network devices involved in the company’s sales in Europe. The backup cell 512 is communicatively coupled to the backup cell 510, and is given the domain name “Company.sales.eur”. As such, the

manager component associated with the backup cell 512 is under the supervisory control of the manager component associated with the domain “Company.sales”.

Correspondingly, the backup cell 514 is concerned with directing backups of network computing devices involved in the Asian sales division. The backup cell 514 is communicatively coupled to the backup cell 510, and has the domain name “Company.sales.asia”. Thus, the manager component for the backup cell 514 is under the supervisory control of the manager component associated with the domain name “Company.sales”.

One should note that in this example the manager components for the backup cell 512 does not have supervisory control over the backup cell 514, and vice versa. In any case, this is possible and can be implemented.

The backup cell 520 contains several hierarchical portions. First, the domain “Company.mktg” is contained in the backup cell 520. The manager component associated with the “Company.mktg” domain exercise supervisory functions for backup cells residing under the “Company.mktg” domain. These other sub-domains are administered and configured from the manager component associated with the “Company.mktg” domain.

Additionally, the backup cell 520 contains the virtual backup cells “Company.mktg.tv” and “Company.mktg.print”, each associated with the backup of network devices associated with the different departments in the “Company.mktg” domain. Each domain has its own virtual manager component exercising control over its own particular administrative domain, and being under the supervisory control of a manager component running on the same backup cell 520.

A backup cell 530 contains a domain named “Company.eng”, responsible for supervisory control of the backup schemes for the network devices in the company’s engineering locations. The backup cell 530 also contains a domain “Company.eng.nj”. The manager component associated with the domain “Company.eng.nj” is responsible for the configuration, administration, and direction of backups of network computing devices for engineering work located in the company’s New Jersey locations.

Nested underneath the backup cell 530 are backup cells 532, 534, and 536, having the domain names “Company.eng.ca”, “Company.eng.tx”, and “Company.eng.jp”, respectively. Each of these backup cells is responsible for the backup of network computing devices at a particular location, and are under the supervisory control of the manager component associated with the domain “Company.eng”.

Additionally, other backup cells 540 and 542 are nested beneath the domain “Company.eng.ca”. The domains “Company.eng.ca.routers” and “Company.eng.ca.gateways” are associated with backup cells for network computing devices associated with specific lines of engineering.

Thus, from the manager component associated with the domain “Company”, an administrator can configure, administer, or direct backup activities for any of the nested backup cells below it in the “”hq”, “sales”, “mktg”, or “eng” domains. Sufficient information on backups and events are replicated up from the lower lying backup cells in the tree to allow the manager component associated with the “Company” domain to perform these supervisory duties. Further, any intervening manager components in the path between a specific domain and the root may perform the supervisory activities.

Thus, from any backup cell on a sub-tree, a manager component associated with that backup cell can supervise, configure, or administer the backup functionality of any backup cell in nested below it. For example, an administrator at the “Company.eng” manager component would be able to configure all the backup cells in with the name “Company.eng.*”, where “*” stands for any sub-domain under the “Company.eng” domain.

Critical events or information regarding a physical backup in a backup cell, such as the information indexed by a media component as it backs up a file and/or data unit, are communicated towards the root. For example, assume that a particular network computing device operating in the backup cell “Company.eng.ca.gateways” fails. If the event is critical enough, news of the event would be replicated to “Company.eng.ca”, and from there to “Company.eng”, and ultimately to “Company”. Thus, actions at any of these backup cells may be asserted to aid the situation. Information regarding the backup process would also be replicated towards the root.

Usually, the events are replicated in an online fashion in real-time. Replication takes place, subject to criticality thresholds, all the way to the root as long as the parent backup cell is reachable. If the parent is unreachable, the underlying backup cell needing to send the information on may periodically spawn a process to check on the reachability of the parent backup cell. If the parent backup cell resumes a reachable state, the message, along with others stored in a queue, are passed upwards to the parent backup cell.

Or, the parent may request a “dump” of meta-data and critical events regarding the status of the system and its children at any time. This dump may be a one level dump,

or may recursively act on all the sub-domains of the sub-domain. This meta-data could include the information regarding the backup event and indexed at the time of backup, information of all domains known to the child backup cell, backup devices and their associated media components in the backup cell, clients and their client components in the backup cell, applications running on the client network devices in the backup cell, related archive files grouped into archive groups on the network devices in the backup cell, sets of related media defining a media group in the backup cell, and all backup devices.

Thus, not only events may be passed upwards, but the state of each backup cell, both physical and virtual, may be passed upwards accordingly. This allows the parent manager component to act in place of the child should it be required to do so. Or, it allows true supervisory control of the child backup cell, as well as the supervisory control over any child backup cells of the child backup cell, and so on.

Additionally, due to the passage of this information, viewing, administering, configuring, and controlling the domains under a particular domain is possible from a root domain. Further, the manager components associated with the sub-domains may be administered from the root domain of the tree or any sub-tree within the main body of the tree structure. Thus, administration en masse is possible for an entire enterprise, division, location, or any other granularity as required. In view of the above detailed description of the present invention and associated drawings, other modifications and variations will now become apparent to those skilled in the art. It should also be apparent that such other modifications and variations may be effected without departing from the spirit and scope of the present invention as set forth in this specification.

We claim:

1. A backup and retrieval system for a network computing system, the network computing system comprising a plurality of groups of network devices storing data, the backup and retrieval system comprising:

a plurality of backup cells comprising:

a backup device executing a backup of the data stored on at least one of the plurality of groups of network devices;

a management component, communicatively coupled to the at least one backup device, controlling the backup of the data to the backup device; and

each of the plurality of backup cells communicatively coupled to at least one other of the plurality of backup cells, and each of the plurality of backup cells adaptable to be controlled by a management component in another of the plurality of backup cells.

2. The backup and retrieval system of claim 1, wherein the backup device is controllable from the management component in another of the plurality of backup cells.

3. The backup and retrieval system of claim 1, wherein the backup device is controllable from the management component in another of the plurality of backup cells via the management component in the same backup cell as the backup device.

4. A backup and retrieval system for a network computing system, the network computing system comprising a first group of network devices storing data, the backup and retrieval system comprising:

a first backup cell comprising:

at least one backup device executing a backup of the data stored on the first group of network devices;

a first manager component, communicatively coupled to the at least one backup device, controlling the backup of the data to the at least one backup device;

a second backup cell communicatively coupled to the first backup cell, the second backup cell comprising:

a second manager component; and

the second manager component controlling the backup of the data to the at least one backup device.

5. The backup and retrieval system of claim 4 wherein the second manager component directly controls the backup of data to the at least one backup device.

6. The backup and retrieval system of claim 4 wherein the second manager component directly controls the backup of data to the at least one backup device via the first manager component.

7. The backup and retrieval system of claim 4, the network computing system comprising a first network device, wherein the first manager component is a software

module executing on the first network device, and the second manager component is a software module.

8. The backup and retrieval system of claim 7, the network computing system further comprising a second network device, wherein the second manager component executes on the second network device.

9. The backup and retrieval system of claim 7 wherein the second manager component executes on the first network device.

10. A backup and retrieval system for a network computing system, the network computing system comprising a first group of network devices containing data, the network computing system further comprising a first network device, the backup and retrieval system comprising:

at least one backup device executing backup functions for the data contained on the first group of network devices;

a first management component executing on the first network device, communicatively coupled to the at least one backup device, controlling the backup of the data to the at least one backup device; and

a second manager component, communicatively coupled to the first network device, the second manager component controlling the backup of the data to the at least one backup device.

11. The backup and retrieval system of claim 10 wherein the second management component executes on the first network device.

12. The backup and retrieval system of claim 10, the network computing system further comprising a second network device, wherein the second management component executes on the first network device.

13. The backup and retrieval system of claim 10, the network computing system further comprising a second group of network devices containing data, wherein the second management component controls a backup of the data contained on the second group of network devices.

14. The backup and retrieval system of claim 10, wherein the backup device is controllable directly from the second management component.

15. The backup and retrieval system of claim 10, wherein the backup device is controllable from the second management component via the first management component.

16. A backup and retrieval system for a network computing system, the network computing system comprising a first group of network devices containing data, the backup and retrieval system comprising:

at least one backup device executing backup functions for the data contained on the first group of network devices;

a first network device, communicatively coupled to the at least one backup device, controlling the backup of the data contained on the first group of network devices to the at least one backup device; and

a second network device, communicatively coupled to the first network device, the second network device the second manager component controlling the backup of the data to the at least one backup device.

17. The backup and retrieval system of claim 16, the network computing system further comprising a second group of network devices containing data, wherein the second network device controls a backup of the data contained on the second group of network devices.

18. The backup and retrieval system of claim 16, wherein the second network device directly controls the backup of the data to the at least one backup device.

19. The backup and retrieval system of claim 16, wherein the second network device controls the backup of the data to the at least one backup device via the first network device.

ABSTRACT

The invention is a hierarchical backup system. The interconnected network computing devices are put into groups of backup cells. A backup cell has a manager software agent responsible maintaining and initiating a backup regime for the network computing devices in the backup cell. The backups are directed to backup devices within the backup cell. Several backup cells can be defined. A manager software agent for a particular cell may be placed into contact with the manager software agent of another cell, by which information about the cells may be passed back and forth. Additionally, one of the software agents may be given administrative control over another software agent with which it is in communication. Thus, the first software agent can direct or alter the parameters of the second software agent to define a new backup regimen for the backup cell controlled by the second software agent. Or, if the second software agent fails or cannot function properly, the first software agent can direct the backup of the second cell. The software agents need not operate on separate computing devices. Additionally, a backup hierarchy may be achieved using the communication and control techniques of the software agents.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY

As a below-named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first, and sole inventor (if only one name is listed below) or an original, first, and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled **HIERARCHICAL BACKUP AND RETRIEVAL SYSTEM**

(check one) ☒ is attached hereto
 ☐ was filed on _____
 as Application Serial No. _____
 and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim the benefit under Title 35, United States Code, §§ 119(e) and 120, of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

_____ (Provisional Application)	_____ (Filing Date)	_____ (Status)
------------------------------------	------------------------	-------------------

I hereby appoint the following attorneys and/or agents to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

James D. Bennett,	Reg. No. 37,550
Michael R. Cannatti,	Reg. No. 34,791
James B. Gambrell,	Reg. No. 17,920
Mark J. Gatschet	Reg. No. 42,569
Dennis W. Gilstad,	Reg. No. 36,810
Gary W. Hamilton,	Reg. No. 31,834
Mira L. Helms	Reg. No. 43,668
H. Dale Langley,	Reg. No. 35,927
Gloria L. Norberg,	Reg. No. 36,706

Russell C. Scott,	Reg. No. 43,103
Adam D. Sheehan,	Reg. No. 42,146
Richard J. Smith,	Reg. No. 30,496
Pete A. Smits,	Reg. No. 39,036
Gary R. Stanford,	Reg. No. 35,689
H. Shannon Tyson, Jr.	Reg. No. 42,193
J. Davis Gilmer	Reg. No. P-44,711

Of: Akin, Gump Strauss, Hauer & Feld, L.L.P.
816 Congress Avenue, Suite 1900
Austin, TX 78701
(512) 499-6200; and

Address all telephone calls to James D. Bennett at telephone no. (512) 499-6200
Address all correspondence to James D. Bennett
Akin, Gump, Strauss, Hauer & Feld, L.L.P.
816 Congress Avenue
1900 Frost Bank Building
Austin, Texas 78701

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

First named inventor:

Full name John Crescenti
Inventor's Signature [Signature] Date 7/1/89
Residence Freehold, New Jersey Citizenship USA
Post Office Address 1 Ivy Road, Freehold, New Jersey 07728

Second named inventor:

Full name Srinivas Kavuri
Inventor's Signature [Signature] Date 7/8/99
Residence Highland Park, New Jersey Citizenship India
Post Office Address 40 Maple Court, Highland Park, New Jersey 08904

Third named inventor:

Full name David Alan Oshinsky
Inventor's Signature [Signature] Date 7/7/99
Residence East Brunswick, New Jersey Citizenship USA
Post Office Address 22 Francis Road, East Brunswick, New Jersey 08816

Fourth named inventor:

Full name Anand Prahlad
Inventor's Signature [Signature] Date 7/7/99
Residence EAST BRUNSWICK, NEW JERSEY Citizenship India
Post Office Address 3 BUCKNELL DRIVE, EAST BRUNSWICK, NJ 08816